

Dual switchmode power supply

2223



- 24 / 115 / 230 VAC supply voltage
- 3.75 kVAC isolation
- 2 adjustable 5...24 VDC outputs
- Output: $\pm 5...24$ VDC, 10...48 VDC
- Short-circuit protection
- Thermal protection against overload



Advanced features

- The power supply is based on switch mode technology to achieve a high efficiency.
- The outputs are adjustable by 2 front potentiometers in the ranges 5...24 VDC.


Application

- Supply for small measuring systems that demand 2 stabilized voltages.
- Either as a combination of positive and negative voltages, or as 2 separate supplies as required.
- The two supplies are galvanically separated with 500 VAC test voltage and can be connected in series or used as two independent supplies with or without common gnd.
- Separation of circuits in safety installations according to PELV/SELV.
- Galvanic isolation between the primary and the secondary voltage is achieved through the double-isolated safety transformer.

Technical characteristics

- Two green LEDs, Power ON 1 and Power ON 2, indicate active outputs.
- By connecting the two outputs in series, 10...48 VDC or $\pm 5...24$ VDC can be achieved.
- The input circuit is protected with a bimetal thermal fuse.
- DC output short circuit protection with current limiter.
- Mounting for a standard 11-pole socket which can be adapted for DIN rail or plate use with PR's 7023 adaptor and 7024 mounting keying.

Connections



Order:

Type	Version	Output 1	Output 2
2223	115 VAC : A	Special (5...24 VDC) : 0	Special (5...24 VDC) : 0
	230 VAC : B	24 VDC : 1	24 VDC : 1
	24 VAC : D	15 VDC : 2	15 VDC : 2
		12 VDC : 3	12 VDC : 3
		5 VDC : 4	5 VDC : 4

Environmental Conditions

Specifications range..... -20°C to +60°C
 Relative humidity..... < 95% RH (non-cond.)
 Protection degree..... IP30

Mechanical specifications

Dimensions (HxWxD)..... 80.5 x 35.5 x 84.5 mm (D is without pins)
 Weight approx..... 400 g

Common specifications**Isolation voltage**

Isolation voltage, test / working..... 3.75 kVAC / 250 VAC
 Isolation output 1 / 2, test / working..... 500 VAC / 50 VAC (75 VDC)
 PELV/SELV..... IEC 61140

Internal consumption..... 4 W
 Effect of supply voltage change..... < ±30 mV (±10%)
 Transformer..... EN 60742
 Transient stability (10%-max. load)..... < 250 mV
 Temperature coefficient..... 0.05% / °C
 EMC immunity influence..... < ±0.5%

Input specifications

Supply voltage..... 21.6...26.4 VAC
 Supply voltage..... 103.5...126.5 VAC
 Supply voltage..... 207...253 VAC
 Frequency..... 50...60 Hz

Output specifications**Current output**

Current limit..... Typ. 100 mA (short circuit)
 Output voltage..... 4.75...25.2 VDC
 Output power..... Max. 7.5 W (total)
 Output current, per channel..... 0.5 A / 5 VDC (2.5 W)
 Output current, per channel..... 0.37 A / 12 VDC (4.5 W)
 Output current, per channel..... 0.30 A / 15 VDC (4.5 W)
 Output current, per channel..... 0.18 A / 24 VDC (4.3 W)
 Load effect (10%-max. load)..... < 1.5% / A
 Output ripple..... < 20 mVRMS

Observed authority requirements

EMC..... 2014/30/EU
 LVD..... 2014/35/EU

Approvals

EAC..... TR-CU 020/2011