

## Isolated universal converter

### 3114

- Input for RTD, TC, Ohm, potentiometer, mA and V
- Slimline housing of 6 mm
- 2-wire supply >15 V
- Output for current and voltage
- Can be supplied separately or installed on power rail, PR 9400



#### Application

- Linearized, electronic temperature measurement with RTD or TC sensor.
- Conversion of linear resistance variation to a standard analog current / voltage signal, i.e. from solenoids and butterfly valves or linear movements with attached potentiometer.
- Power supply and signal isolator for 2-wire transmitters.
- Process control with standard analog output.
- Galvanic separation of analog signals and measurement of floating signals.
- The device can be mounted in Safe area or in Zone 2 and Cl. 1 Div 2. area.

#### Advanced features


- When 3114 is used in combination with the 4501 display / programming front and ConfigMate 4590, all operational parameters can be modified to suit any application.

#### Technical characteristics


- A green / red front LED indicates normal operation and malfunction.
- 3-port 2.5 kVAC galvanic isolation.

#### Connections

##### Input signals:



##### Output signals and power supply:



*Safe Area or  
Zone 2 & Cl. 1, Div. 2, gr. A-D*

Order:

Type
3114

## Environmental Conditions

Specifications range.....	-25°C to +70°C
Storage temperature.....	-40°C to +85°C
Calibration temperature.....	20...28°C
Relative humidity.....	< 95% RH (non-cond.)
Protection degree.....	IP20
Installation in.....	Pollution degree 2 & measurement / overvoltage cat. II

## Mechanical specifications

Dimensions (HxWxD).....	113 x 6.1 x 115 mm
Weight approx.....	70 g
DIN rail type.....	DIN EN 60715/35 mm
Wire size.....	0.13 x 2.5 mm <sup>2</sup> / AWG 26...12 stranded wire
Screw terminal torque.....	0.5 Nm
Vibration: 2...25 Hz.....	±1.6 mm
Vibration: 25...100 Hz.....	±4 g

## Common specifications

### Supply

Supply voltage.....	16.8...31.2 VDC
---------------------	-----------------

### Isolation voltage

Isolation voltage, test / working.....	2.5 kVAC / 300 VAC (reinforced)
Zone 2 / Div. 2.....	250 VAC

### Response time

Temperature input (0...90%, 100...100%).....	≤ 1 s
mA / V input (0...90%, 100...100%).....	≤ 400 ms
Fuse.....	400 mA SB / 250 VAC
Max. required power.....	1.2 W
Internal consumption.....	0.4 W (typ.) / 0.65 W (max.)
Signal / noise ratio.....	> 60 dB
Programming.....	ConfigMate 4590
Accuracy.....	Better than 0.1% of selected range
EMC immunity influence.....	< ±0.5% of span
Extended EMC immunity: NAMUR NE 21, A criterion, burst.....	< ±1% of span

## Input specifications

### RTD input

RTD type.....	Pt10, Pt20, Pt50, Pt100, Pt200, Pt250, Pt300, Pt400, Pt500, Pt1000, Ni50, Ni100, Ni120, Ni1000
---------------	--

Cable resistance per wire (max.).....

50 Ω

Sensor current.....

Nom. 0.2 mA

Effect of sensor cable resistance (3-/4-wire).....

< 0.002 Ω / Ω

Sensor error detection.....

Yes

Short circuit detection.....

< 15 Ω

### TC input

Thermocouple type.....	B, E, J, K, L, N, R, S, T, U, W3, W5, LR
------------------------	--

CJC via internally mounted sensor.....

±(2.0°C + 0.4°C \* Δt)

Δt = Internal temperature-ambient temperature

Sensor error detection..... Yes

Sensor error current: When detecting / else..... Nom. 2 μA / 0 μA

### Current input

Measurement range..... 0...23 mA

Programmable measurement ranges..... 0...20 and 4...20 mA

Input resistance..... Nom. 20 Ω + PTC 50 Ω

### Voltage input

Measurement range..... 0...12 VDC

Programmable measurement ranges..... 0/0.2...1, 0/1...5, 0/2...10 VDC

Input resistance..... Nom. 10 MΩ

2-wire transmitter supply..... > 15 V / 20 mA

## Output specifications

### Current output

Signal range..... 0...23 mA

Programmable signal ranges..... 0...20 / 4...20 / 20...0 and 20...4 mA

Load (@ current output)..... ≤ 600 Ω

Load stability..... ≤ 0.01% of span / 100 Ω

Sensor error indication..... 0 / 3.5 / 23 mA / none

NAMUR NE 43 Upscale/Downscale..... 23 mA / 3.5 mA

Current limit..... ≤ 28 mA

### Voltage output

Signal range..... 0...10 VDC

Programmable signal ranges..... 0/0.2...1; 0/1...5 ; 0/2...10; 1...0.2/0; 5...1/0; 10...2/0 V

Load (@ voltage output)..... ≥ 10 kΩ

\*of span..... = of the currently selected measurement range

## Observed authority requirements

EMC..... 2014/30/EU

LVD..... 2014/35/EU

RoHS..... 2011/65/EU

## Approvals

ATEX 2014/34/EU..... KEMA 10ATEX0147 X, II 3 G Ex nA IIC T4 Gc

IECEx..... KEM 10.0068X

FM..... 3041043-C

DNV Marine..... Stand. f. Certific. No. 2.4

GL..... V1-7-2

UL..... UL 61010-1

EAC..... TR-CU 020/2011

EAC Ex TR-CU 012/2011..... RU C-DK.GB08.V.00410

CCOE..... P337347/1