1004D3 and the 1005E3

### **API Bottom Loading Couplers**

The 1004D3 and the 1005E3 are the latest generation in API Bottom Loading Couplers from OPW. A proven performer at major oil terminals around the world just got better...

#### Safer

- 5-Cam Design Ensures easy alignment; tight connection to adaptor and resists side forces while loading
- Fully Interlocked Dual interlocks ensure the D3 cannot be opened unless it is properly connected to an API adaptor

#### Cleaner

- Superior Sealing Simple and reliable smartseal design consisting of dual high-performance O-rings
- High-Performance Seals Special fluorocarbon seal compound provides compatibility across most products including gasoline, diesel, biodiesel and ethanol\*

#### **Faster**

- Operation New stainless steel "ergo" handle design provides easy, smooth operation
- Maintenance All pins and small threads have been eliminated to provide quick, easy access to all critical components
- Nose seal can be replaced easily without having to remove coupler from rack
- No special tools required
- Can be completely rebuilt in minutes





1005E3 (Small Handles)



<sup>\*</sup>Other seals available upon request.

### **Design Parameters**

| <b>Max Design Pressure</b>          | 125 psig (8.6 bar)   |
|-------------------------------------|--|
| Max Allowable<br>Working Pressure*  | 75 psig (5 bar)  |
| Max Flow Rate                       | 600 gpm, 135 m³/h  |
| Temperature Range                   | <ul> <li>Fluorocarbon -20°F to 400°F (-29°C to 204°C)</li> <li>Buna-N -20°F to 250°F (-29°C to 121°C)</li> <li>EPDM -50°F to 225°F (-46°C to 107°C)</li> </ul> |
| Weight:                             | 21 lbs (9.5 kg)  |
| Pressure Drop<br>(At Max Flow Rate) | 2-5 psig (0.24 bar)*   |

<sup>\*</sup>Unit tested to 300 psi in closed position to withstand excessive thermal expansion pressures. Reference API standard RP-1004 for additional information.

#### **Materials**

| Body, Sleeve, Poppet                                  | Aluminum        |
|---|-----------------|
| Shaft, Cam Arms,<br>Interlocks, Drive Link,<br>Handle | Stainless Steel |
| Cylinder  | Aluminum        |

### **Seal Replacement Kits**

The 1004D3 SRK (Seal Replacement Kit) includes everything needed to replace all seals in the D3 API Bottom Loading Coupler. Seal replacement kits are always recommended as spare parts.

| Seal Material: | Model         | Kit Part #       |
|----------------|---------------|------------------|
| Buna-N         | 1004D3/1005E3 | 1004D3SRK - 0401 |
| Fluorocarbon   | 1004D3/1005E3 | 1004D3SRK - 0402 |
| EPDM           | 1004D3/1005E3 | 1004D3SRK - 0404 |

#### **Selection Guide**



# **Accessories**



## **1004DRN Drain Adaptor**

- Allows operator to easily, safely drain loading arm
- Fits any API Bottom Loading Coupler



### **1004PA Parking Adaptor**

- Use to neatly store and secure loading arms while not in use
- Can be provided with standpost and/or proximity switch

